

Industry · Membrane Keyboards · Desktop Keyboards

Membrane Keyboard GFT-105 Table-top Version with Touchpad

Waferthin and Shock-Resistant Membrane Keyboard with integrated Touchpad.



Artikel-Nr.	KF1300
Bezeichnung	GFT-105-T-Touch-USB-Ger
Ausführung	USB, German
Varianten	7 Ausführungen

Membrane

waterproof

Keyboards

with Touchpad

Images



Product description

The GFT-105 membrane keyboard is one of the most flexible keyboards developed by GeBE. The most important difference regarding traditional membrane keyboards is the possibility to feel free to exclusively decide about form and color of the keys as well as form of the individual housing.

The 1,5 mm thick keyboard has convex and colorful designed membrane keys based on the different standard RAL-colors. Therefore the keyboard is especially user-friendly regarding ergonomical input.

Available as Frontplate Version

Features

- The key mechanics of the GFT-105 is based on 11 mm metal dome including gold contacts, as well as a 16 mm key pitch. The controller supports PS/2 or USB interface.

- The GFT-105 is available with integrated touchpad or as a matrix. The touchpad version has the NUM-Keys positioned above the function keys. The IP 65 keyboard permit an application under damp and dusty conditions. It is especially designed for industrial, medical or laboratory purposes.
- The 'Full-N-Key-Rollover' that is integrated in the controller automatically recognizes accidental input errors or wrong key combinations. However, the auto repeat function always identifies the last pressed key.
- The software of the GCK-990 also supports the Ghost-Key-Detection. This function makes the use of decoupling diodes unnecessary.
- Customized solutions concerning form, color and design
- Dust- and waterproof up to DIN IP 65 on the front
- Available in a robust polystyrol plastic table housing or as keyboard mat
- Available as a matrix without housing and controller
- Up to 144 keys can be connected in a matrix, including a function key (Fn) that controls alternative key assignments for 50 keys maximum
- Controller supports Full-N-Key-Rollover
- Mit USB interface

Technical data

Mechanical data

Housing	Table-top housing
Housing	Polystyrene (HIPS)
Degree of Protection	IP65
Dimensions	330 x 160,20 x 10,0 mm
Cable Length	180 cm

Keys

Key Technology	metal dome
Number of Keys	105
Keyboard Layout	German or Swiss or US or France
Actuation Force	2 N
Stroke Travel	0,3 mm
Key Legend	silk screen

Electric Data

Interface	USB or PS/2
Operating Voltage	5 V
Operating Current	4 mA

Environment

Operating Temperature	from 0 °C to +70 °C
Storage Temperature	to +80 °C

Quality

Live time	about 1 million key strokes
-----------	-----------------------------

Technical data

delivery form

Weight	0,570 kg
--------	----------

Order & get advice

Technical advice, samples and quantity pricing on request. Talk to us — we will configure the right version for your application.

+49 89.894399-0

sales@tastaturen.com

www.tastaturen.com

Subject to technical changes and errors. All information without guarantee. © 2026 GeBE Computer & Peripherie GmbH