

Accessories · Cables

M-19 Metallic Switch

M-19 Metallic Switch for use in frontplates and housings



Artikel-Nr.	ZT1353
Bezeichnung	ZTS- M19 Metalltaste
Ausführung	M19 Zink-Druckguss Taster
Varianten	4 Ausführungen

Short Travel

waterproof

integratable

Keys

Matrix Output

Product description

The M-19 metallic switch was designed for integration into front pannels and housings. The switch has a durable housing and has an extremely flat front facia of only 1mm which offers little surface for vandalism.

The mounting is via a M19 nut, which is included.

The button can be laser engraved on customer demand.

Some existing patterns are as follows: A..Z, 0..9, +, -, /, *, =, #, Cursorpfeile, %, CRTL, RETURN, SHIFT, LOCK, STOP, ENTER, BACK, LINE, EIN, AUS, AUF, AB, ON, OFF, UP, DOWN, HIGH, LOW, ON/OFF, START

To avoid the turning of the switch and the legends the shaft of the switch is D-shaped (see technical drawing). A sealing gasket is also included.

A screwable connector for the outgoing leads is included as well. It may be removed if the leads are to be souldered. We can also supply special switches with pins of ø2mm instead of ø1mm for easier souldering.

When the key of the switch is pressed down completely, the power is taken up by the housing and not by the switching element to improve the durability.

All applications where low-cost vandalresistant keys are needed. Especially in such devices that are not surveyed and therefore often subject to vandalism.

Features

- Durable metal housing
- IP65 water and dust proof
- Easily integratable
- It is possible to engrave the keys
- Elegant design
- Great tactile feedback
- Easily servicable
- Standard M19 mounting

- Flat facia and boilt to a minimal depth
- Various possibilities for connecting the outgoing leads
- Very competitive price
- Infoterminals
- Public kiosks
- Doorbells
- Entry control systems
- Car-washes
- Elevators
- etc.

Technical data

Mechanical data

Dimensions 21,4 x 25,55 mm

Housing Zinkdruckguß

Degree of Protection IP65

Keys

Number of Keys 1

Operational Life >1 mio. keystrokes min.

Actuation Force 3,7 N

Temperature

Operating Temperature from -25 °C to 60 °C

Additional Information

Diameter M19

Accessories



Kabel zum Anschluss von 2 Tasten (L+R) an Trackball mit integriertem Controller

ZK1245

Kabel zum Anschluss von 3 Tasten (L+R) an Trackball mit integriertem Controller

ZK1342

Order & get advice

Technical advice, samples and quantity pricing on request. Talk to us — we will configure the right version for your application.

+49 89.894399-0

sales@tastaturen.com

www.tastaturen.com

Subject to technical changes and errors. All information without guarantee. © 2026 GeBE Computer & Peripherie GmbH